


CADENAS DE PLACAS SERIE AL



CHAIN N°	Juego	Paso		Placa		Pin		*Carga Admisible	Carga de Rotura	Peso Aprox.
		P		Altura	Espesor	Diámetro	Longitud			
		pulgadas	mm	H (mm)	T (mm)	D (mm)	L (mm)			
AL422	2x2						8.30	1499	1723	0.39
AL444	4x4	1/2"	12.70	10.20	1.50	3.96	14.40	2998	3589	0.74
AL466	6x6						20.50	4487	5374	1.13
AL522	2x2						11.05	2498	2916	0.64
AL534	3x4	5/8"	15.875	13.00	2.00	5.08	17.00	3752	4691	1.10
AL544	4x4						19.40	4986	6363	1.25
AL566	6x6						27.50	7485	9565	1.79
AL622	2x2						13.00	3406	4527	0.87
AL644	4x4	3/4"	19.05	15.50	2.35	5.94	22.70	6801	8035	1.70
AL666	6x6						32.20	10207	12094	2.53
AL688	8x8						42.20	13603	15969	3.37
AL822	2x2						16.20	5904	6995	1.57
AL844	4x4	1"	25.40	20.40	3.10	7.92	29.40	11798	13827	3.08
AL866	6x6						44.20	17692	20629	4.62
AL888	8x8						55.50	23596	24983	6.12
AL1022	2x2						19.60	8616	10921	2.51
AL1044	4x4	1 - 1/4"	31.75	24.80	3.90	9.53	36.40	17233	20761	4.95
AL1066	6x6						52.30	25849	32151	7.39
AL1088	8x8						68.50	34466	42950	9.83
AL1222	2x2						24.30	12247	15408	3.65
AL1244	4x4	1 - 1/2"	38.1	30.00	4.70	11.10	43.80	24493	30560	7.05
AL1266	6x6						63.20	36740	43470	10.50
AL1288	8x8						82.60	48986	57960	14.03
AL1444	4x4	1 - 3/4"	44.45	36.20	5.60	12.70	51.30	30846	42175	9.80
AL1466	6x6						74.50	46264	63262	14.66
AL1644	4x4						58.00	39004	53310	12.90
AL1666	6x6	2"	50.80	41.40	6.40	14.21	83.80	58510	79904	19.27
AL1688	8x8						109.50	78007	106610	25.64

* La carga de trabajo ideal es el 20% de la capacidad de carga admisible.